

SPANLOAD

...SAFETY FIRST

POLYESTER

ENDLESS FLAT SLINGS

EINDLOZE HIJSBANDEN VLAK

HEBEBÄNDER BANDSCHLINGEN

BEARS YOUR BUSINESS



SPANLOAD

...SAFETY FIRST



BEARS YOUR BUSINESS

Polyester Slings since 2007.

Spanload stands for Safety & Efficiency. Standardized for volume handlings. Tailor made for heavy projects cargo... always at the top of the quality standards.

SPANLOAD...Safety First | Bears your Business



EN1492-1 | EN1492-2



- Highest safety for your workers.
- Long durability | Reusable.
- Consistent quality | highest standards.
- 100% compliant to EN 1492.
- At the top of the quality standards.
- Always with Safety Factor 7:1.
- Production according to ISO 9001
- Inspection certificate for each production batch.
- Any length as per customer request.
- Customer name print on Spanload slings possible.
- Standardized sizes available from stock.

Typical stock sizes | EN 1492-1 | Safety Factor 7:1

| COLOR CODE | WORK LOAD LIMIT | SF | WIDTH [mm] | EFFECTIVE LENGTH | COMPLETE LENGTH |
|------------|-----------------|-----|------------|------------------|-----------------|
| WHITE | 500 KG | 7:1 | 25mm | 0.75 MTR | 1.50 MTR |
| WHITE | 750 KG | 7:1 | 35mm | 1.25 MTR | 2.50 MTR |
| WHITE | 750 KG | 7:1 | 35mm | 1.75 MTR | 3.50 MTR |
| VIOLET | 1000 KG | 7:1 | 30mm | 1.25 MTR | 2.50 MTR |
| VIOLET | 1000 KG | 7:1 | 30mm | 1.75 MTR | 3.50 MTR |
| WHITE | 1500 KG | 7:1 | 50mm | 1.25 MTR | 2.50 MTR |
| WHITE | 1500 KG | 7:1 | 50mm | 1.75 MTR | 3.50 MTR |
| GREEN | 2000 KG | 7:1 | 60mm | 1.75 MTR | 3.50 MTR |
| GREEN | 2000 KG | 7:1 | 60mm | 2.00 MTR | 4.00 MTR |
| YELLOW | 3000 KG | 7:1 | 90mm | 1.75 MTR | 3.50 MTR |
| YELLOW | 3000 KG | 7:1 | 90mm | 2.50 MTR | 5.00 MTR |

Products according to:



EN1492-1 | EN1492-2



SPANLOAD

... SAFETY FIRST

"In the past we used slings from various suppliers but we did not always know who produced them. 3 years ago we decided to replace them by Spanload slings. Using one brand only which we can rely on for 100% makes me feel very comfortable, because now I know my workers are safe when handling our products"

... steel constructor from Belgium

"We handle various goods in our port and need tailor made lifting solutions for different cargos. Spanload offers all we need."

... port operator from The Netherlands



BEARS YOUR BUSINESS

Instruction for Spanload Sling Use

| WORK LOAD LIMITS IN TONS | | | | | | |
|--------------------------|--------|---------------|------------|--------------|----------------|-----------------|
| WLL | COLOR | STRAIGHT LIFT | CHOKE LIFT | BASKET HITCH | | |
| | | | | | | |
| | | | | PARALLEL | 0 < 45 degrees | 45 < 60 degrees |
| | | M = 1 | M = 0.8 | M = 2 | M = 1.4 | M = 1 |
| 0.5 TON | WHITE | 0.5 | 0.4 | 1.0 | 0.7 | 0.5 |
| 0.75 TON | WHITE | 0.75 | 0.6 | 1.25 | 1.05 | 0.75 |
| 1 TON | VIOLET | 1.0 | 0.8 | 2.0 | 1.4 | 1.0 |
| 1.5 TON | WHITE | 1.5 | 1.2 | 3.0 | 2.1 | 1.5 |
| 2 TON | GREEN | 2.0 | 1.6 | 4.0 | 2.8 | 2.0 |
| 3 TON | YELLOW | 3.0 | 2.4 | 6.0 | 4.2 | 3.0 |
| 4 TON | GREY | 4.0 | 3.2 | 8.0 | 5.6 | 4.0 |
| 5 TON | RED | 5.0 | 4.0 | 10.0 | 7.0 | 5.0 |
| 6 TON | BROWN | 6.0 | 4.8 | 12.0 | 8.4 | 6.0 |
| 8 TON | BLUE | 8.0 | 6.4 | 16.0 | 11.2 | 8.0 |
| 10 TON | ORANGE | 10.0 | 8.0 | 20.0 | 14.0 | 10.0 |

M = MODE FACTOR FOR SYMMETRICAL LOADING AND HANDLING TOLERANCE FOR SLINGS | EN1492-1



SPANLOAD

... SAFETY FIRST

IMPORTER | PRODUCER

Van Dijk Supplies
Phone: +31 (0) 26 4720368
Fax: +31 (0)26 4722741
Mail: info@spanload.com
Zipcode: 6666 ZG
Address: P.O. Box 20, Heteren

WWW.SPANLOAD.COM

BEARS YOUR BUSINESS

SPANLOAD product brochures:

- *Polyester Sling Endless Flat* | EN1492-1
- Polyester Sling Eye-Eye | EN1492-1
- Polyester Sling Endless Round | EN1492-2
- Polyester Ratches | EN12195-2

Products according to:



EN1492-1 | EN1492-2

